



Overview

HDI Interactive freestanding digital signage solutions allow you to broadcast a variety of interactive content to your target audience.

This contemporary communication solution outperforms traditional signs, pamphlets and posters by offering dynamic integrated audio, video and imagery. Whatever your objective may be this digital kiosk solution offers informative, interactive and content-rich media to bolster user-experience.

Features

- 2x 10W integrated speakers
- Easy-clean gloss finish
- Compatible with Windows, MacOS & Linux
- LG display panel
- Full-HD resolution (1920 x 1080px)
- Metal & Aluminium housing with toughened glass

Screen parameters

Screen size	47"
Panel	LG
Resolution	1080x1920
View angle	178 (H) / 178 (V)
Display colour	16.7M
Brightness	350cd/m2
Contrast	3000:1
Response time	6ms
Life time	50,000 hrs (Min.)
Display area	1039.68mm x 584.82mm
Use time	24 hour
I/O	USBx1, HDMI INx3, VGA INx1

Touch

Technology	Infrared
Touch points	6 point
Response time	≤8ms

Power

Consumption (max)	90W
Voltage	AC 100-240V 50/60Hz

Structure

Screen size	1800mmx696mmx45mm
Screen material	Toughened glass

Other

Operating temperature	0°C ~ 40°C
Storage temperature	(-10°C ~ 60°C)
Storage humidity	10% ~ 60% RH Non-Condensing
Working humidity	20% ~ 80% RH Non-Condensing
Outer material	Metal & Aluminium
Speaker	2x10W

Distributed by: